



20

DoP001-LMP-18.09.2020

Litex Membrane Board

1	Unique identification code of the product	Litex Membrane Board
2	Intended uses of the construction product	Membrane board for walls and floors in wet rooms
3	Manufacturer	Litex AS, Pindsleveien 4, 3221 Sandefjord, Norge
4	Authorised representative	Not relevant
5	System of attestation of conformity	System 2+
6.b	Guideline for European Technical Approval:	ETAG 022-3: November 2010
	Number for European Technical Approval:	ETA-20/0296
	Technical Assessment Body:	ETA-Danmark A/S
	Notified Body:	SINTEF NO 1071

7. Declared performance

Essential characteristic	Performance	Method of verification
Reaction to fire	NPD*	
Release of dangerous substance	None	
Water vapour resistance	7800 m	NS-EN-ISO 12572
equiv. air layer thickness, S _d -value		
Water tightness	Watertight	NS-EN 14891
Crack bridging ability	NPD*	
Bond strength	Category 2: ≥ 0,3 MPa	NS-EN 14891
Scratching resistance	NPD*	
Joint bridging ability	Category 0: Not relevant	ETAG 022-3
Watertightness around	Category 2: Pass	ETAG 022-3
penetrations		
Dimensional stability	NPD*	
Resistance to temperature	Category 1: Pass	ETAG 022-3
Resistance to water	Watertight	ETAG 022-3
Resistance to alkalinity	Category 2: Pass	ETAG 022-3
Thickness	13, 20, 30, 50 mm	

^{*}NPD = No Performance Determined

DECLARATION OF PERFORMANCE

DoP001-LMP-18.09.2020



The performance of the product identified in point 1 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Name and function	Place and date	Signature
David Gusland	Sandefjord, 18.09.2020	
Product- and innovation manager		(1) cevil (sull
		Dan Gui