



20

DoP002-LMD-21.10.2020

Litex Membrane Sheet

1	Unique identification code of the product	Litex Membrane Sheet
2	Intended uses of the construction product	Membrane sheet for walls and floors in wet rooms
3	Manufacturer	Litex AS, Pindsleveien 4, 3221 Sandefjord, Norge
4	Authorised representative	Not relevant
5	System of attestation of conformity	System 2+
6.b	Guideline for European Technical Approval: Number for European Technical Approval: Technical Assessment Body: Notified Body:	ETAG 022-2: November 2010 ETA-19/0142 Deutsches Institut für Bautechnik, DIBt Säurefliesner-Vereinigung e. V. DE 1212

7. Declared performance

Essential characteristic	Performance	Method of verification
Reaction to fire	class E	EN 13501-1
Release of dangerous substance	NPD*	
Water vapour resistance equiv. air layer thickness, S _d -value	45,8 m	NS-EN-ISO 12572
Water tightness	Watertight	NS-EN 14891
Crack bridging ability	Category 3: 1,5 mm	ETAG 022-2
Bond strength	Category 2: ≥ 0,3 MPa	NS-EN 14891
Scratching resistance	NPD*	
Joint bridging ability	Category 2: Pass	ETAG 022-2
Watertightness around penetrations	Category 2: Pass	ETAG 022-2
Dimensional stability	NPD*	
Resistance to temperature	Pass	ETAG 022-2
Resistance to water	Category 2: ≥ 0,3 MPa	ETAG 022-2
Resistance to alkalinity	Category 2: Pass	ETAG 022-2
Thickness	0,6 mm	

*NPD = No Performance Determined

DECLARATION OF PERFORMANCE

DoP002-LMD-21.10.2020



The performance of the product identified in point 1 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Name and function	Place and date	Signature
David Gusland Product- and innovation manager	Sandefjord, 21.10.2020	